

Standard Features:

- High Performance **Armorflex®** High gloss with **BuffBack®** Gel coat for superior colour retention, blister resistance and quicker gloss recovery of aged gel coats.
- Vinyl Ester Resin skin coat to abate osmotic transfer and enhance long term blister resistance.
- Thru Bolted High impact Rigid vinyl rub rail with Stainless Steel insert.
- Self bailing fibre glass liner
- High Visibility Windshield
- Rotary steering
- Stainless Steel deck hardware
- Navigation/Anchor lights
- Horn with Stainless Steel grill
- Glove box
- Soft-Touch Grip steering wheel
- Stainless steel Thru-hulls
- 2 Heavy Duty Wipers
- High Output Auto Bilge pump
- Insulated Bait well
- Anchor Locker
- Welded Stainless Steel bow rail
- Stainless Steel Grab handle at Port bulkhead
- 2.8 gal Porta Potti
- Lined cuddy cabin with deluxe cushions, Interior lighting, side shelves, additional storage compartments under cushions, and locking cuddy door
- Locking swivel pedestal slider (With pedestal seating)
- Seating Options – 2 sleeper, 1 pedestal + 1 sleeper or 2 pedestals
- Large Easy Access Side Storage compartments, 2 large Fish/storage seat bases
- New Helm station - with area for large GPS/Find-er/Radar combo unit



LOA	20'2"/6.15M	Weight	2380lbs/1200kg
Beam	8'2"/2.5M	Max. H.P.	225 O/B
Cockpit Depth	32"/0.81M	Deadrise	20 deg. (at transom)
Fuel Capacity	60 U.S. gal/240L	Transom Hgt	25"

Options:

- Gel Coat Hull Accent Colour
- Padded interior side panels
- Auxiliary plug-in
- Stainless Steel Steering Wheel
- Snap-in carpet
- Stainless Steel Bow roller
- Hydraulic steering
- Swim grid (one or two step)
- Trim Tabs
- Bait well pump, bait well timer
- 12V Raw Water Washdown
- 5.0 gal. Porta Potti
- 4pc slope top w/ travel boot or Camper top
- See thru drop curtain with zippered door

Disclaimer: Standard Features and Options subject to change - confirm with Dealer



Fish/Storage Box



Stainless Thru-Hulls



See Thru Drop Curtain Available

DOUBLE EAGLE MARINE INC.

www.doubleeagleboats.com info@doubleeagleboats.com

Ph: 604.941.0929 Fax: 604.941.0923